

University of Nebraska - Lincoln

DigitalCommons@University of Nebraska - Lincoln

Nebraska Tractor Tests

Tractor Test and Power Museum, The Lester F.
Larsen

1-1-1982

Test 1425: Ford 4110 (8x4) Diesel 8-speed

Tractor Museum

University of Nebraska-Lincoln, TractorMuseumArchives@unl.edu

Follow this and additional works at: <http://digitalcommons.unl.edu/tractormuseumlit>



Part of the [Applied Mechanics Commons](#)

Museum, Tractor, "Test 1425: Ford 4110 (8x4) Diesel 8-speed" (1982). *Nebraska Tractor Tests*. Paper 1740.
<http://digitalcommons.unl.edu/tractormuseumlit/1740>

This Article is brought to you for free and open access by the Tractor Test and Power Museum, The Lester F. Larsen at DigitalCommons@University of Nebraska - Lincoln. It has been accepted for inclusion in Nebraska Tractor Tests by an authorized administrator of DigitalCommons@University of Nebraska - Lincoln.

NEBRASKA TRACTOR TEST 1425 — FORD 4110 (8 X 4) DIESEL 8 SPEED

POWER TAKE-OFF PERFORMANCE

Power Hp (kW)	Crank shaft speed rpm	Fuel Consumption			Temperature °F (°C)			Barometer inch Hg (kPa)
		gal/hr (l/h)	lb/hp.hr (kg/kW.h)	Hp.hr/gal (kW.h/l)	Cooling medium	Air wet bulb	Air dry bulb	
MAXIMUM POWER AND FUEL CONSUMPTION								
Rated Engine Speed—Two Hours (PTO Speed—660 rpm)								
49.26 (36.73)	2200	3.165 (11.981)	0.443 (0.270)	15.57 (3.066)	204 (95.4)	59 (14.9)	76 (24.2)	29.000 (97.929)
Standard Power Take-off Speed (540 rpm)—One Hour								
44.06 (32.86)	1799	2.744 (10.387)	0.429 (0.261)	16.06 (3.164)	205 (96.1)	59 (14.9)	75 (23.8)	28.990 (97.895)
VARYING POWER AND FUEL CONSUMPTION—Two Hours								
43.17 (32.19)	2268	2.893 (10.951)	0.462 (0.281)	14.92 (2.939)	192 (89.2)	59 (15.0)	75 (23.9)
0.00 (0.00)	2326	1.031 (3.903)	170 (76.9)	59 (15.0)	75 (23.9)
21.87 (16.31)	2300	1.901 (7.196)	0.599 (0.365)	11.51 (2.267)	175 (79.4)	59 (15.0)	75 (23.9)
49.83 (37.16)	2199	3.189 (12.072)	0.441 (0.268)	15.63 (3.078)	201 (93.9)	59 (15.0)	75 (23.9)
11.01 (8.21)	2312	1.449 (5.485)	0.907 (0.552)	7.60 (1.497)	168 (75.6)	59 (15.0)	75 (23.9)
32.61 (24.32)	2284	2.397 (9.074)	0.507 (0.308)	13.60 (2.680)	177 (80.6)	59 (15.0)	75 (23.9)
Av Av	26.41 (19.69)	2.143 (8.112)	0.560 (0.340)	12.32 (2.427)	181 (82.6)	59 (15.0)	75 (23.9)	28.997 (97.917)

DRAWBAR PERFORMANCE

Power Hp (kW)	Drawbar pull lbs (kN)	Speed mph (km/h)	Crank- shaft speed rpm	Slip %	Fuel Consumption			Temp. °F (°C)			Barom. inch Hg (kPa)
					gal/hr (l/h)	lb/hp.hr (kg/kW.h)	Hp.hr/gal (kW.h/l)	Cool- ing med	Air wet bulb	Air dry bulb	
Maximum Available Power—Two Hours 5th Gear											
39.80 (29.68)	3023 (13.44)	4.94 (7.95)	2201	6.54	3.081 (11.665)	0.534 (0.325)	12.92 (2.544)	189 (87.2)	61 (16.1)	65 (18.3)	28.790 (97.220)
75% of Pull at Maximum Power—Ten Hours 5th Gear											
32.18 (23.99)	2318 (10.31)	5.21 (8.38)	2279	4.85	2.654 (10.045)	0.569 (0.346)	12.13 (2.389)	178 (80.9)	62 (16.8)	68 (19.7)	28.725 (97.000)
50% of Pull at Maximum Power—Two Hours 5th Gear											
21.76 (16.23)	1546 (6.87)	5.28 (8.50)	2276	3.35	2.085 (7.891)	0.661 (0.402)	10.44 (2.056)	177 (80.3)	68 (20.0)	75 (23.9)	28.760 (97.118)
50% of Pull at Reduced Engine Speed—Two Hours 6th Gear											
21.77 (16.23)	1546 (6.88)	5.28 (8.50)	1563	3.21	1.686 (6.381)	0.534 (0.325)	12.91 (2.543)	174 (78.9)	69 (20.3)	74 (23.3)	28.730 (97.017)
MAXIMUM POWER IN SELECTED GEARS											
29.05 (21.66)	5691 (25.31)	1.91 (3.08)	2272	14.74	2nd Gear			175 (79.2)	59 (15.0)	60 (15.6)	28.760 (97.118)
37.88 (28.24)	5188 (23.08)	2.74 (4.41)	2199	13.82	3rd Gear			190 (87.8)	64 (17.8)	69 (20.6)	28.810 (97.287)
39.65 (29.57)	3480 (15.48)	4.27 (6.88)	2202	7.76	4th Gear			191 (88.1)	65 (18.3)	70 (21.1)	28.800 (97.253)
40.59 (30.27)	3091 (13.75)	4.92 (7.92)	2200	6.79	5th Gear			196 (90.8)	65 (18.3)	71 (21.7)	28.800 (97.253)
39.97 (29.81)	2038 (9.07)	7.36 (11.84)	2200	4.22	6th Gear			193 (89.2)	66 (18.9)	73 (22.8)	28.790 (97.220)

LUGGING ABILITY IN 5th GEAR

Crankshaft Speed rpm	2200	1993	1762	1546	1323	1110	882
Pull—lbs (kN)	3091 (13.75)	3280 (14.59)	3420 (15.21)	3533 (15.72)	3641 (16.20)	3655 (16.26)	3509 (15.61)
Increase in Pull %	0	6	11	14	18	18	14
Power—Hp (kW)	40.59 (30.27)	38.85 (28.97)	35.66 (26.59)	32.18 (24.00)	28.29 (21.10)	23.79 (17.74)	18.22 (13.59)
Speed—Mph (km/h)	4.92 (7.92)	4.44 (7.15)	3.91 (6.29)	3.42 (5.50)	2.91 (4.69)	2.44 (3.93)	1.95 (3.13)
Slip %	6.79	7.11	7.54	7.86	8.29	8.29	8.08

Department of Agricultural Engineering

Dates of Test: April 23 to May 14, 1982

Manufacturer: FORD MOTOR COMPANY,
Ford Tractor Operations, 2500 East Maple
Road, Troy, Michigan 48084

FUEL, OIL AND TIME: Fuel No. 2 Diesel
Cetane No. 46.5 (rating taken from oil company's
inspection data) **Specific gravity converted to 60°/
60° (15°/15°) 0.8282 Fuel weight 6.896 lbs/gal
(0.826 kg/l) Oil SAE 30 API service classifica-
tion SE/SF-CC/CD To motor 1.353 gal (5.120 l)
Drained from motor 1.151 gal (4.357 l) Trans-
mission and final drive lubricant Ford 134 fluid
Total time engine was operated 43.0 hours.**

**ENGINE: Make Ford Diesel Type three cylin-
der vertical Serial No. *K629779* Crankshaft
lengthwise Rated rpm 2200 Bore and stroke 4.4"
× 4.4" (112 mm × 112 mm) Compression ratio
16.3 to 1 Displacement 201 cu in (3294 ml) Start-
ing system 12 volt Lubrication pressure Air
cleaner two paper elements Oil filter one full
flow cartridge Fuel filter one paper element
Muffler vertical Cooling medium temperature
control one thermostat.**

**CHASSIS: Type standard Serial No.
C681208 Tread width rear 64" (1625 mm) to
80" (2032 mm) front 52" (1320 mm) to 80" (2032
mm) Wheel base 77.5" (1969 mm) Center of grav-
ity (without operator or ballast, with minimum
tread, with fuel tank filled and tractor serviced for
operation) Horizontal distance forward from cen-
ter-line of rear wheels 28.8" (732 mm) Vertical dis-
tance above roadway 28.3" (719 mm) Horizontal
distance from center of rear wheel tread 0" (0 mm)
to the right/left Hydraulic control system direct
engine drive Transmission selective gear fixed
ratio Advertised speeds mph (km/h) first 1.4 (2.2)
second 2.2 (3.5) third 3.2 (5.1) fourth 4.7 (7.6)
fifth 5.4 (8.7) sixth 7.9 (12.7) seventh 11.5 (18.5)
eighth 16.8 (27.0) reverse 2.0 (3.2), 2.9 (4.7), 4.2
(6.7), 6.1 (9.8) Clutch single plate dry disc oper-
ated by foot pedal Brakes wet multiple disc oper-
ated by two foot pedals which can be locked
together Steering power assist Turning radius
(on concrete surface with brake applied) right
114" (2.89 m) left 114" (2.89 m) (on concrete sur-
face without brake) right 136" (3.45 m) left 136"
(3.45 m) Turning space diameter (on concrete
surface with brake applied) right 233" (5.92 m) left
233" (5.92 m) (on concrete surface without brake)
right 275" (6.98 m) left 275" (6.98 m) Power take-
off 540 rpm at 1799 engine rpm.**

REPAIRS and ADJUSTMENTS: The radiator
fan shroud was replaced following the limber up
period. All fuel injectors were replaced during
preliminary PTO tests.

TRACTOR SOUND LEVEL WITHOUT CAB		dB(A)	
Maximum Available Power—Two Hours		96.5	
75% of Pull at Maximum Power—Ten Hours		95.0	
50% of Pull at Maximum Power—Two Hours		94.0	
50% of Pull at Reduced Engine Speed—Two Hours		92.0	
Bystander in 8th gear		86.0	
TIRES, BALLAST AND WEIGHT		With Ballast	Without Ballast
Rear Tires	—No., size, ply & psi (kPa)	Two 16.9-24; 6; 16 (110)	Two 16.9-24; 6; 16 (110)
Ballast	—Liquid (each)	648 lb (294 kg)	None
	—Cast Iron (each)	680 lb (308 kg)	None
Front Tires	—No., size, ply & psi (kPa)	Two 7.50-16; 6; 40 (275)	Two 7.50-16; 6; 40 (275)
Ballast	—Liquid (each)	None	None
	—Cast Iron (each)	65 lb (29 kg)	None
Height of Drawbar		15.5 in (395 mm)	15.5 in (395 mm)
Static Weight with Operator—Rear		5665 lb (2570 kg)	3010 lb (1366 kg)
	—Front	1835 lb (832 kg)	1705 lb (773 kg)
	—Total	7500 lb (3402 kg)	4715 lb (2139 kg)

REMARKS: All test results were determined from observed data obtained in accordance with SAE and ASAE test codes or official Nebraska test procedure. For the maximum power tests, the fuel temperature at the injection pump return was maintained at 151°F (66.0°C). Five gears were chosen between 15% slip and 10 mph (16.1 km/h). The fuel tank level indicator did not function during test.

We, the undersigned, certify that this is a true and correct report of official Tractor Test **1425**.

LOUIS I. LEVITICUS
Engineer-in-Charge

K. VON BARGEN
W. E. SPLINTER
L. L. BASHFORD
Board of Tractor Test Engineers



Ford 4110 (8 X 4) Diesel