

University of Nebraska - Lincoln

DigitalCommons@University of Nebraska - Lincoln

Nebraska Tractor Tests

Tractor Test and Power Museum, The Lester F.
Larsen

1-1-1965

Test 889: Ford 3000 4-Speed (Gasoline)

Tractor Museum

University of Nebraska-Lincoln, TractorMuseumArchives@unl.edu

Follow this and additional works at: <http://digitalcommons.unl.edu/tractormuseumlit>



Part of the [Applied Mechanics Commons](#)

Museum, Tractor, "Test 889: Ford 3000 4-Speed (Gasoline)" (1965). *Nebraska Tractor Tests*. Paper 1271.
<http://digitalcommons.unl.edu/tractormuseumlit/1271>

This Article is brought to you for free and open access by the Tractor Test and Power Museum, The Lester F. Larsen at DigitalCommons@University of Nebraska - Lincoln. It has been accepted for inclusion in Nebraska Tractor Tests by an authorized administrator of DigitalCommons@University of Nebraska - Lincoln.

NEBRASKA TRACTOR TEST 889 - FORD 3000 4-SPEED GASOLINE

POWER TAKE-OFF PERFORMANCE

Hp	Crankshaft speed rpm	Fuel Consumption		Hp-hr per gal	Temperature Degrees F			Barometer inches of Mercury
		Gal per hr	Lb per hp-hr		Cooling medium	Air wet bulb	Air dry bulb	
MAXIMUM POWER AND FUEL CONSUMPTION								
Rated Engine Speed—Two Hours								
39.17	2100	3.273	0.508	11.97	196	56	75	29.110
Standard Power Take-off Speed (540 rpm)—One Hour								
30.64	1485	2.510	0.498	12.21	196	56	75	29.100
VARYING POWER AND FUEL CONSUMPTION—TWO HOURS								
34.53	2177	2.959	0.521	11.67	193	57	76
0.00	2327	1.213	184	56	75
17.79	2243	2.121	0.725	8.39	190	57	76
39.78	2100	3.354	0.513	11.86	198	56	75
9.03	2278	1.667	1.123	5.42	187	57	75
26.19	2203	2.500	0.581	10.48	191	57	76
Av 21.22	2221	2.302	0.660	9.22	190	56	75	29.107

DRAWBAR PERFORMANCE

Hp	Drawbar pull lbs	Speed miles per hr	Crankshaft speed rpm	Slip of drivers %	Fuel Consumption		Temp Degrees F			Barometer inches of Mercury
					Gal per hr	Lb per hp-hr	Hp-hr per gal	Cooling med	Air wet bulb	

VARYING DRAWBAR POWER AND FUEL CONSUMPTION WITH BALLAST

Maximum Available Power—Two Hours—5th Gear (2nd direct)											
33.04	2538	4.88	2100	5.43	3.270	0.602	10.10	194	64	87	28.890
75% of Pull at Maximum Power—Ten Hours—5th Gear (2nd direct)											
27.40	1987	5.17	2189	3.88	2.799	0.621	9.79	189	59	80	28.688
50% of Pull at Maximum Power—Two Hours—5th Gear (2nd direct)											
19.04	1340	5.33	2220	2.48	2.285	0.730	8.33	191	62	89	28.818

MAXIMUM POWER WITH BALLAST

30.98	4622	2.51	2180	13.76	1st Gear (1st under)	185	54	67	28.945	
32.28	3932	3.08	2103	9.76	2nd Gear (2nd under)	190	54	67	28.945	
33.64	3198	3.94	2103	7.39	3rd Gear (1st direct)	190	56	69	28.945	
32.63	2620	4.67	2099	5.86	4th Gear (3rd under)	191	56	69	28.945	
34.30	2648	4.86	2097	5.86	5th Gear (2nd direct)	191	58	74	28.945	
33.18	2053	6.06	2097	4.34	6th Gear (1st over)	190	59	75	28.945	
32.91	1703	7.25	2102	3.67	7th Gear (3rd direct)	192	59	75	28.945	
32.75	1648	7.45	2106	3.56	8th Gear (2nd over)	190	62	82	28.940	
32.31	1194	10.15	2109	2.36	9th Gear (4th under)	190	62	82	28.935	
32.30	1100	11.01	2099	1.78	10th Gear (3rd over)	190	62	82	28.930	

MAXIMUM POWER WITHOUT BALLAST

32.43	2558	4.75	2096	9.05	5th Gear (2nd direct)	192	60	79	28.520	
-------	------	------	------	------	-----------------------	-----	----	----	--------	--

VARYING DRAWBAR PULL AND TRAVEL SPEED WITH BALLAST—5th Gear (2nd direct)

Pounds pull	2648	2732	2763	2801	2881	2762
Horsepower	34.30	31.62	28.32	25.12	22.23	17.67
Crankshaft speed, rpm	2097	1879	1667	1461	1258	1040
Miles per hour	4.86	4.34	3.84	3.36	2.89	2.40
Slip of drivers, %	5.86	6.18	6.18	6.29	6.40	6.18

TIRES, BALLAST and WEIGHT

		With Ballast	Without Ballast
Rear tires	—No, size, ply & psi	Two 14.9-24; 4; 12	Two 14.9-24; 4; 12
Ballast	—Liquid	650 lb each	None
	—Cast iron	560 lb each	None
Front tires	—No, size, ply & psi	Two 6.00-16; 4; 28	Two 6.00-16; 4; 28
Ballast	—Liquid	None	None
	—Cast iron	None	None
Height of drawbar		21 inches	22 inches
Static weight	—Rear	4610 lb	2190 lb
	—Front	1620 lb	1600 lb
Total weight with operator		6405 lb	3965 lb

Department of Agricultural Engineering

Dates of Test: APRIL 20 TO MAY 6, 1965

Manufacturer: FORD MOTOR COMPANY, BIRMINGHAM, MICHIGAN

FUEL, OIL and TIME Fuel regular gasoline Octane No Motor 85.2 Research 92.3 (rating taken from oil company's typical inspection data) Specific gravity converted to 60°/60° 0.7308 Weight per gallon 6.083 lb Oil SAE 10W API service classification MS, DM To motor 1.486 gal Drained from motor 1.454 gal Transmission and final-drive lubricant SAE 80 EP Total time engine was operated 49½ hours.

ENGINE Make Ford gasoline Type 3 cylinder vertical Serial No NG003164M4 Crankshaft mounted lengthwise Rated rpm 2100 Bore and stroke 4.2" x 3.8" Compression ratio 8 to 1 Displacement 157.95 cu in Carburetor size 1¼" Ignition system battery Cranking system 12 volt electric Lubrication pressure Air cleaner dry type with replaceable pleated paper element Oil filter replaceable cotton blend element Fuel filter edge type in sediment bowl Muffler was used Cooling medium temperature control thermostat.

CHASSIS Type standard Serial No 100811 Tread width rear 52" to 76" front 52" to 80" Wheel base 75.8" Center of gravity (without operator or ballast, with minimum tread, with fuel tank filled and tractor serviced for operation) Horizontal distance forward from center-line of rear wheels 32.8" Vertical distance above roadway 25.2" Horizontal distance from center of rear wheel tread 0" to the right/left Hydraulic control system direct engine drive Transmission selective gear fixed ratio Advertised speeds mph first 4.2 second 5.0 third 7.4 fourth 15.5 reverse 4.4 Clutch single plate dry disc operated by foot pedal Brakes internal expanding shoe operated by two foot pedals which can be locked Steering mechanical with power assist Turning radius (on concrete surface with brake applied) right 117" left 117" (on concrete surface without brake) right 129" left 129" Turning space diameter (on concrete surface with brake applied) right 240" left 240" (on concrete surface without brake) right 267" left 267" Belt pulley 1323 rpm at 1950 engine rpm diam 9" face 6.5" Belt speed 3117 fpm Power take-off 546 rpm at 1500 engine rpm.

REPAIRS and ADJUSTMENTS The governor was replaced before the beginning of the PTO runs.

REMARKS All test results were determined from observed data obtained in accordance with the SAE and ASAE test code.

It was necessary to limit the pull in first gear because of the stability formula. Eleventh and twelfth gears were not run as they exceeded 15 mph.

This tractor was equipped with the standard 4-speed transmission plus an optional auxiliary overdrive-underdrive transmission.

We, the undersigned, certify that this is a true and correct report of official Tractor Test 889.

L. F. LARSEN
Engineer-in-Charge

G. W. STEINBRUEGGE, Chairman
J. J. SULEK
D. E. LANE
Board of Tractor Test Engineers