

University of Nebraska - Lincoln

DigitalCommons@University of Nebraska - Lincoln

Nebraska Tractor Tests

Tractor Test and Power Museum, The Lester F.
Larsen

1-1-1965

Test 888: Ford 3000 8-Speed (Gasoline)

Tractor Museum

University of Nebraska-Lincoln, TractorMuseumArchives@unl.edu

Follow this and additional works at: <http://digitalcommons.unl.edu/tractormuseumlit>



Part of the [Applied Mechanics Commons](#)

Museum, Tractor, "Test 888: Ford 3000 8-Speed (Gasoline)" (1965). *Nebraska Tractor Tests*. Paper 1270.
<http://digitalcommons.unl.edu/tractormuseumlit/1270>

This Article is brought to you for free and open access by the Tractor Test and Power Museum, The Lester F. Larsen at DigitalCommons@University of Nebraska - Lincoln. It has been accepted for inclusion in Nebraska Tractor Tests by an authorized administrator of DigitalCommons@University of Nebraska - Lincoln.

NEBRASKA TRACTOR TEST 888 - FORD 3000 8-SPEED GASOLINE

POWER TAKE-OFF PERFORMANCE

Hp	Crank-shaft speed rpm	Fuel Consumption		Hp-hr per gal	Temperature Degrees F			Barometer inches of Mercury
		Gal per hr	Lb per hp-hr		Cooling medium	Air wet bulb	Air dry bulb	
MAXIMUM POWER AND FUEL CONSUMPTION								
Rated Engine Speed—Two Hours								
37.84	2100	3.257	0.524	11.62	190	64	76	28.917
Standard Power Take-off Speed (540 rpm)—One Hour								
34.62	1811	2.898	0.509	11.95	190	67	79	28.910
VARYING POWER AND FUEL CONSUMPTION—TWO HOURS								
33.70	2202	2.984	0.539	11.29	191	71	86
0.00	2313	1.248	162	70	86
17.22	2250	2.111	0.746	8.16	180	71	88
37.33	2100	3.289	0.536	11.35	194	72	89
8.71	2275	1.682	1.175	5.18	169	72	88
25.56	2227	2.574	0.613	9.93	190	73	90
Av 20.42	2228	2.315	0.690	8.82	181	71	88	28.850

DRAWBAR PERFORMANCE

Hp	Draw-bar pull lbs	Speed miles per hr	Crank-shaft speed rpm	Slip of drivers %	Fuel Consumption		Hp-hr per gal	Temp Degrees F			Barometer inches of Mercury
					Gal per hr	Lb per hp-hr		Cooling med	Air wet bulb	Air dry bulb	
VARYING DRAWBAR POWER AND FUEL CONSUMPTION WITH BALLAST											
Maximum Available Power—Two Hours—4th Gear											
32.52	2481	4.92	2098	5.18	3.263	0.610	9.97	192	62	70	28.880
75% of Pull at Maximum Power—Ten Hours—4th Gear											
26.55	1877	5.30	2234	3.92	2.867	0.657	9.26	171	43	44	28.891
50% of Pull at Maximum Power—Two Hours—4th Gear											
19.35	1353	5.36	2231	2.75	2.359	0.742	8.20	175	63	72	28.835
MAXIMUM POWER WITH BALLAST											
27.53	5059	2.04	2187	13.94	2nd Gear		175	60	64	28.910	
32.15	3407	3.54	2107	7.54	3rd Gear		189	60	64	28.910	
32.81	2498	4.93	2105	5.31	4th Gear		184	62	66	28.885	
33.21	2539	4.90	2098	5.36	5th Gear		190	62	66	28.890	
32.34	1541	7.87	2101	3.15	6th Gear		184	60	68	28.900	
29.37	820	13.43	2102	1.23	7th Gear		178	60	68	28.900	
MAXIMUM POWER WITHOUT BALLAST											
32.93	2569	4.81	2101	8.38	4th Gear		180	39	41	29.080	

VARYING DRAWBAR PULL AND TRAVEL SPEED WITH BALLAST—4th Gear

Pounds pull	2498	2638	2636	2689	2718	2767	2641
Horsepower	32.81	30.72	27.36	24.58	21.21	19.77	13.81
Crankshaft speed, rpm	2105	1870	1668	1470	1258	1152	841
Miles per hour	4.93	4.37	3.89	3.43	2.93	2.68	1.96
Slip of drivers, %	5.31	5.47	5.58	5.69	5.90	5.90	5.80

TIRES, BALLAST and WEIGHT

		With Ballast	Without Ballast
Rear tires	—No, size, ply & psi	Two 14.9-24; 4; 14	Two 14.9-24; 4; 12
Ballast	—Liquid	640 lb each	None
	—Cast iron	800 lb each	None
Front tires	—No, size, ply & psi	Two 6.00-16; 4; 32	Two 6.00-16; 4; 28
Ballast	—Liquid	None	None
	—Cast iron	None	None
Height of drawbar		20 inches	22 inches
Static weight	—Rear	5130 lb	2250 lb
	—Front	1690 lb	1670 lb
Total weight with operator		6995 lb	4095 lb

Department of Agricultural Engineering

Dates of Test: APRIL 20 TO APRIL 27, 1965

Manufacturer: FORD MOTOR COMPANY, BIRMINGHAM, MICHIGAN

FUEL, OIL and TIME Fuel regular gasoline Octane No Motor 85.2 Research 92.3 (rating taken from oil company's typical inspection data) Specific gravity converted to 60°/60° 0.7308 Weight per gallon 6.083 Oil SAE 10W API service classification MS DM To motor 1.487 gal Drained from motor 1.390 gal Transmission and final-drive lubricant Ford Oil ESN-M2C-77A Total time engine was operated 41½ hours.

ENGINE Make Ford gasoline Type 3 cylinder vertical Serial No NG003215M4 Crankshaft mounted lengthwise Rated rpm 2100 Bore and stroke 4.2" x 3.8" Compression ratio 8 to 1 Displacement 157.95 cu in Carburetor size 1¼" Ignition system battery Cranking system 12 volt electric Lubrication pressure Air cleaner dry type with pleated paper element Oil filter full flow replaceable cotton blend element Fuel filter edge type filter in sediment bowl Muffler was used Cooling medium temperature control thermostat.

CHASSIS Type standard Serial No C101954 Tread width rear 52" to 76" front 52" to 80" Wheel base 75.8" Center of gravity (without operator or ballast, with minimum tread, with fuel tank filled and tractor serviced for operation) Horizontal distance forward from centerline of rear wheels 32.8" Vertical distance above roadway 25.2" Horizontal distance from center of rear wheel tread 0" to the right/left Hydraulic control system direct engine drive Transmission selective gear fixed ratio Advertised speeds mph first 1.5 second 2.3 third 3.8 fourth 5.0 fifth 5.0 sixth 8.0 seventh 13.4 eighth 18.3 reverse 2.3 and 8.4 Clutch single plate dry disc in combination with PTO clutch operated by single foot pedal Brakes internal expanding shoe operated by two foot pedals which can be locked Steering mechanical with power assist Turning radius (on concrete surface with brake applied) right 117" left 117" (on concrete surface without brake) right 129" left 129" Turning space diameter (on concrete surface with brake applied) right 240" left 240" (on concrete surface without brake) right 267" left 267" Belt pulley 1141 rpm at 2050 engine rpm diam 10.25" face 6.5" Belt speed 3061 fpm Power take-off 537 rpm at 1800 engine rpm.

REPAIRS and ADJUSTMENTS No repairs or adjustments.

REMARKS All test results were determined from observed data obtained in accordance with the SAE and ASAE test code.

First gear was not run as it was necessary to limit the pull in second gear because of the stability formula. Eighth gear was not run because it exceeded 15 mph.

We, the undersigned, certify that this is a true and correct report of official Tractor Test 888.

L. F. LARSEN

Engineer-in-Charge

G. W. STEINBRUEGGE, Chairman

J. J. SULEK

D. E. LANE

Board of Tractor Test Engineers

The University of Nebraska Agricultural Experiment Station
E. F. Frolik, Dean; H. H. Kramer, Director, Lincoln, Nebraska