

University of Nebraska - Lincoln

DigitalCommons@University of Nebraska - Lincoln

---

Nebraska Tractor Tests

Tractor Test and Power Museum, The Lester F.  
Larsen

---

1-1-1966

## Test 933: Ford 5000 Select-O-Speed (Gasoline)

Tractor Museum

University of Nebraska-Lincoln, [TractorMuseumArchives@unl.edu](mailto:TractorMuseumArchives@unl.edu)

Follow this and additional works at: <http://digitalcommons.unl.edu/tractormuseumlit>



Part of the [Applied Mechanics Commons](#)

---

Museum, Tractor, "Test 933: Ford 5000 Select-O-Speed (Gasoline)" (1966). *Nebraska Tractor Tests*. Paper 1309.  
<http://digitalcommons.unl.edu/tractormuseumlit/1309>

This Article is brought to you for free and open access by the Tractor Test and Power Museum, The Lester F. Larsen at DigitalCommons@University of Nebraska - Lincoln. It has been accepted for inclusion in Nebraska Tractor Tests by an authorized administrator of DigitalCommons@University of Nebraska - Lincoln.

# NEBRASKA TRACTOR TEST 933 – FORD 5000 SELECT-O-SPEED GASOLINE

## POWER TAKE-OFF PERFORMANCE

Hp	Crankshaft speed rpm	Fuel Consumption			Temperature Degrees F				Barometer inches of Mercury
		Gal per hr	Lb per hp-hr	Hp-hr per gal	Cooling medium	Air wet bulb	Air dry bulb		
<b>MAXIMUM POWER AND FUEL CONSUMPTION</b>									
<b>Rated Engine Speed—Two Hours</b>									
58.49	2100	5.001	0.521	11.70	195	55	75	29.040	
<b>Standard Power Take-off Speed (540 rpm)—One Hour</b>									
55.33	1901	4.684	0.516	11.81	195	54	75	29.010	
<b>VARYING POWER AND FUEL CONSUMPTION—TWO HOURS</b>									
50.79	2144	4.595	0.552	11.05	195	54	75	.....	
0.00	2313	1.830	.....	.....	187	54	75	.....	
26.52	2228	3.262	0.750	8.13	193	54	75	.....	
57.16	2100	4.964	0.530	11.51	196	54	75	.....	
13.38	2260	2.543	1.159	5.26	192	54	74	.....	
38.80	2186	3.891	0.612	9.97	194	54	75	.....	
Av 31.11	2205	3.514	0.689	8.85	193	54	75	28.990	

## DRAWBAR PERFORMANCE

Hp	Drawbar pull lbs	Speed miles per hr	Crankshaft speed rpm	Slip of drivers %	Fuel Consumption			Temp Degrees F			Barometer inches of Mercury
					Gal per hr	Lb per hp-hr	Hp-hr per gal	Cooling med	Air wet bulb	Air dry bulb	
<b>VARYING DRAWBAR POWER AND FUEL CONSUMPTION WITH BALLAST</b>											
<b>Maximum Available Power—Two Hours—6th Gear</b>											
49.51	4310	4.31	2101	5.38	5.036	0.620	9.83	194	41	42	28.645
<b>75% of Pull at Maximum Power—Ten Hours—6th Gear</b>											
39.98	3312	4.53	2178	4.06	4.396	0.670	9.09	195	31	33	28.964
<b>50% of Pull at Maximum Power—Two Hours—6th Gear</b>											
29.05	2351	4.63	2206	3.05	3.786	0.795	7.67	194	40	41	28.610
<b>MAXIMUM POWER WITH BALLAST</b>											
38.79	7073	2.06	2171	10.25	4th Gear	.....	184	40	40	28.700	
50.37	5756	3.28	2103	7.44	5th Gear	.....	186	40	40	28.700	
50.47	4400	4.30	2099	5.47	6th Gear	.....	190	40	40	28.700	
49.76	3733	5.00	2102	4.58	7th Gear	.....	195	39	39	28.690	
48.57	2803	6.50	2097	3.35	8th Gear	.....	197	39	40	28.600	
45.38	1592	10.69	2100	1.88	9th Gear	.....	194	39	40	28.600	
<b>MAXIMUM POWER WITHOUT BALLAST</b>											
48.38	4396	4.13	2102	11.04	6th Gear	.....	193	52	60	29.150	

## VARYING DRAWBAR PULL AND TRAVEL SPEED WITH BALLAST—6th Gear

Pounds pull	4400	4611	4804	4814	4707	4662
Horsepower	50.47	47.34	44.08	38.41	32.35	26.46
Crankshaft speed, rpm	2099	1885	1689	1471	1263	1045
Miles per hour	4.30	3.85	3.44	2.99	2.58	2.13
Slip of drivers, %	5.47	5.85	5.85	6.09	5.85	5.97

## TIRES, BALLAST and WEIGHT

	With Ballast		Without Ballast	
<b>Rear tires</b>	Two 16.9-30; 6; 16		Two 16.9-30; 6; 16	
<b>Ballast</b>	865 lb each		None	
	Cast iron		None	
<b>Front tires</b>	Two 7.50-16; 4; 24		Two 7.50-16; 4; 20	
<b>Ballast</b>	103 lb each		None	
	Cast iron		None	
<b>Height of drawbar</b>	23½ inches		25 inches	
<b>Static weight with operator—Rear</b>	7390 lb		3710 lb	
	Front		2010 lb	
	Total		5720 lb	

The University of Nebraska Agricultural Experiment Station  
E. F. Frolik, Dean; H. H. Kramer, Director, Lincoln, Nebraska

## Department of Agricultural Engineering

Dates of Test: APRIL 13 TO APRIL 22, 1966

Manufacturer: FORD MOTOR COMPANY,  
BIRMINGHAM, MICHIGAN

**FUEL, OIL and TIME** Fuel regular gasoline Octane No Motor 84.5 Research 92.6 (rating taken from oil company's typical inspection data) Specific gravity converted to 60°/60° 0.7325 Weight per gallon 6.098 lb Oil SAE 10W API service classification MS, DM To motor 1.716 gal Drained from motor 1.459 gal Transmission lubricant Ford Oil ESNM2C41-A Final drive lubricant Ford Oil ESNM2C53-A Total time engine was operated 44 hours.

**ENGINE Make** Ford gasoline Type 4 cylinder vertical Serial No RG106288M25 Crankshaft mounted lengthwise Rated rpm 2100 Bore and stroke 4.2" x 4.2" Compression ratio 8.0 to 1 Displacement 233 cu in Carburetor size 1½" Ignition system battery Cranking system 12 volt electric Lubrication pressure Air cleaner oil washed wire mesh Oil filter full flow replaceable paper element Oil cooler heat exchanger in lower radiator tank for transmission oil Fuel filter edge type filter in sediment bowl Muffler was used Cooling medium temperature control thermostat.

**CHASSIS Type** standard Serial No C1243075 Tread width rear 52" to 80" front 52" to 80" Wheel base 87.5 Center of gravity (without operator or ballast, with minimum tread, with fuel tank filled and tractor serviced for operation) Horizontal distance forward from centerline of rear wheels 27.30" Vertical distance above roadway 32.95" Horizontal distance from center of rear wheel tread 0.02" to the right Hydraulic control system direct engine drive Transmission fixed ratio operator controlled full range power shifting Advertised speeds mph first 1.0 second 1.5 third 1.7 fourth 2.3 fifth 3.6 sixth 4.6 seventh 5.3 eighth 6.9 ninth 11.1 tenth 16.4 reverse 3.1 and 4.6 Clutch multiple disc wet clutches within transmission hydraulically operated Brakes wet double disc operated by two foot pedals that can be locked Steering mechanical with power assist Turning radius (on concrete surface with brake applied) right 111" left 111" (on concrete surface without brake) right 141" left 141" Turning space diameter (on concrete surface with brake applied) right 249" left 249" (on concrete surface without brake) right 294" left 294" Belt pulley 1072 rpm at 2050 engine rpm diam 11" face 6.5" Belt speed 3087 fpm Power take-off 540 rpm at 1900 engine rpm.

**REPAIRS and ADJUSTMENTS** No repairs or adjustments.

**REMARKS** All test results were determined from observed data obtained in accordance with the SAE and ASAE test code.

First, second, and third gears were not run as it was necessary to limit the pull in fourth gear because of the stability formula. Tenth gear was not run as it exceeded 15 mph.

We, the undersigned, certify that this is a true and correct report of official Tractor Test 933.

L. F. LARSEN

Engineer-in-Charge

G. W. STEINBRUEGGE, Chairman

J. J. SULEK

D. E. LANE

Board of Tractor Test Engineers