

LEON

"Material Handling Excellence"

Hydraulic Forced Ejection

Land Scrapers

LEON Land Scraper Quick Reference

LEON Model	Hydraulic Forced Ejection	Dolly Wheel	Straight Hitch	Heaped Capacity	Tandem Series	GPS-Laser Ready
M 650	✓	✓		6.51 cu. yd. (4.98 cu. m)		✓
M 1000	✓	✓	✓	10.12 cu. yd. (7.74 cu. m)	✓	✓
M 1350	✓	✓	✓	13.38 cu. yd. (10.21 cu. m)	✓	✓
M 1700	✓	✓	✓	16.93 cu. yd. (12.94 cu. m)	✓	✓
M 2050	✓	✓	✓	20.37 cu. yd. (15.55 cu. m)	✓	✓

1000



Heaped Capacity, cu. yd (cu. m)	10.12 (7.74)	Overall Height, inch (m)	65 (165)
Struck Capacity, cu. yd (cu. m)	6.63 (5.07)	Weight, lbs (kg)	8000 (3636)
Drawbar Horsepower, HP (KW)	130 (97)	Frost Blade, inch (cm)	3/4 x 10 x 54 (1.9 x 25 x 138)
Maximum Drawbar, HP (KW)	225 (168)	Rims	8 Bolt
Clearance, inch (cm)	11 (28)	Guarded Push Off Cylinder, inch (cm) diameter	4 (10.2)
Spreading Depth, inch (cm)	0 to 14 (35.6)	Twin Lift Cylinders, inch (cm) diameter	3-1/2 (8.9)
Cutting Depth, inch (cm)	0 to 8 (20)	Twin Gate Cylinders, inch (cm) diameter	3 (7.6)
Cutting Width, inch (cm)	85 (216)	Standard Front Tires	16.5L x 16.1 -10 Ply Rib
Steering Control, inch (cm) Ball Type	3-1/2 (8.9)	Standard Rear Tires	21.5L x 16.1 -10 Ply Rib
Overall Length, inch (m)	275 (698)	Optional Front Tires	N/A
Overall Width, inch (m)	100 (254)	Optional Rear Tires	N/A

Heaped Capacity, cu. yd (cu. m)	13.38 (10.21)	Overall Height, inch (m)	80 (203)
Struck Capacity, cu. yd (cu. m)	10.60 (8.10)	Weight, lbs (kg)	9000 (4090)
Drawbar Horsepower, HP (KW)	200 (150)	Frost Blade, inch (cm)	3/4 x 10 x 54 (1.9 x 25 x 138)
Maximum Drawbar, HP (KW)	425 (318)	Rims	8 Bolt/10 Bolt
Clearance, inch (cm)	11 (28)	Guarded Push Off Cylinder, inch (cm) diameter	4-1/2 (10.5)
Spreading Depth, inch (cm)	0 to 14 (35.6)	Twin Lift Cylinders, inch (cm) diameter	4 (10.1)
Cutting Depth, inch (cm)	0 to 8 (20)	Twin Gate Cylinders, inch (cm) diameter	3 (7.6)
Cutting Width, inch (cm)	85 (216)	Standard Front Tires	21.5L x 16.1 -10 Ply Rib
Steering Control, inch (cm) Ball Type	4-7/8 (12.4)	Standard Rear Tires	18.4L x 26 -10 Ply Diamond Back
Overall Length, inch (m)	299 (840)	Optional Front Tires	Soft Trac Design
Overall Width, inch (m)	100 (254)	Optional Rear Tires	N/A

1350



Heaped Capacity, cu. yd (cu. m)	16.93 (12.94)	Overall Height, inch (m)	80 (203)
Struck Capacity, cu. yd (cu. m)	10.60 (8.10)	Weight, lbs (kg)	12 200 (5545)
Drawbar Horsepower, HP (KW)	200 (150)	Frost Blade, inch (cm)	3/4 x 10 x 54 (1.9 x 25 x 138)
Maximum Drawbar, HP (KW)	425++ (318)	Rims	8 Bolt
Clearance, inch (cm)	10.5 (26.7)	Guarded Push Off Cylinder, inch (cm) diameter	3 (7.6)
Spreading Depth, inch (cm)	0 to 14 (35.6)	Twin Lift Cylinders, inch (cm) diameter	4 (10.1)
Cutting Depth, inch (cm)	0 to 11 (28)	Twin Gate Cylinders, inch (cm) diameter	3 (7.6)
Cutting Width, inch (cm)	102 (259)	Standard Front Tires	21.5L x 16.1 -10 Ply Rib
Steering Control, inch (cm) Ball Type	4-7/8 (12.4)	Standard Rear Tires	18.4L x 26 -10 Ply Diamond Back
Overall Length, inch (m)	331 (840)	Optional Front Tires	21.5L x 16.1 -10 Ply Soft Trac Design



1700

CONTINUED →



2050 DOLLY WHEEL

Heaped Capacity, cu. yd (cu. m)	20.37 (15.55)	Overall Height, inch (cm)	80 (203)
Struck Capacity, cu. yd (cu. m)	15.79 (12.05)	Weight, lbs (kg)	13 400 (6091)
Drawbar Horsepower, HP (KW)	200 (150)	Frost Blade, inch (cm)	3/4 x 10 x 54 (1.9 x 25 x 138)
Maximum Drawbar, HP (KW)	425 ++ (318)	Rims	10 Bolt
Clearance, inch (cm)	10.5 (26.7)	Guarded Push Off Cylinder, inch (cm) diameter	3-1/2 (9)
Spreading Depth, inch (cm)	0 to 14 (35.6)	Twin Lift Cylinders, inch (cm) diameter	4 (10.1)
Cutting Depth, inch (cm)	0 to 11 (28)	Twin Gate Cylinders, inch (cm) diameter	3 (7.6)
Cutting Width, inch (cm)	102 (259)	Standard Front Tires	18.4L x 26 -10 Ply Diamond Back
Steering Control, inch (cm) Ball Type	4-7/8 (12.4)	Standard Rear Tires	23.1L x 26 -10 Diamond Back
Overall Length, inch (cm)	349 (840)	Optional Front Tires	20.5L x 25 -16 Ply Super Grip
Overall Width, inch (cm)	116 (294)	Optional Rear Tires	23.5L x 25 -16 Ply Super Grip

Heaped Capacity cu. yd (cu. m)	20.37 (15.55)	Overall Height, inch (cm)	80 (203)
Struck Capacity, cu. yd (cu. m)	15.79 (12.05)	Weight, lbs (kg)	14 000 (6364)
Drawbar Horsepower, HP (KW)	200 (150)	Frost Blade, inch (cm)	3/4 x 10 x 54 (1.9 x 25 x 138)
Maximum Drawbar, HP (KW)	425++ (318)	Rims	10 Bolt
Clearance, inch (cm)	10.5 (26.7)	Guarded Push Off Cylinder, inch (cm) diameter	3-1/2 (9)
Spreading Depth, inch (cm)	0 to 14 (35.6)	Twin Lift Cylinders, inch (cm) diameter	4 (10.1)
Cutting Depth, inch (cm)	0 to 11 (28)	Twin Gate Cylinders, inch (cm) diameter	3 (7.6)
Cutting Width, inch (cm)	102 (259)	Standard Front Tires	N/A
Steering Control	N/A	Standard Rear Tires	23.1L x 26 -10 Ply Diamond Back
Overall Length, inch (cm)	349 (840)	Optional Front Tires	N/A
Overall Width, inch (cm)	116 (294)	Optional Rear Tires	23.5L x 26 -16 Ply Super Grip



2050 SH



GZ PULL SCRAPER

- Choice of 12, 14, 16 ft. Widths
- Transport Width 12 Ft. (9'8"), 14 Ft. (11'2"), 16 Ft. (12'8")
- Carrying Capacity 12ft.(3 cu yd), 14ft. (4 cu yd), 16ft. (5 cu yd)
- Ripple Formed Moldboard for cleaner roll off of materials
- Standard Swivel Hitch Tongue (Optional Clevis Swivel Hitch Available)
- All Hoses and Hydraulics Included
- Manual Steering/Offset Adjustment Standard (Hydraulic Control Optional)
- Blade Height 32"
- Overall Length 20 Ft.
- Tires - 16.5L x 22.5
- Hydraulic Cushion Valve Standard
- Replaceable High Carbon Cutting Edge
- Bolt-On Folding End Plates (Optional)
- 300 Maximum Tractor PTO Horsepower
- Overall Height 88 "
- Weight Boxes Provided
- All season use for grading, landscaping, drainage, and snow removal, and so much MORE!



Designed, Tested & Manufactured
in North America

LEONS MFG COMPANY INC.

135 York Road East
Yorkton, Saskatchewan
Canada S3N 3Z4
.....

Toll Free: 1-800-667-1581
Fax: 1-306-782-1884
Email: sales@leonsmfg.com
www.leonsmfg.com