



Pblt Of Atlanta, Llc (P801)
172 Van Mar Blvd.
Jackson, Georgia 30233

MILLER INDUSTRIES
8503 Hilltop Dr
Ooltewah, Tennessee 37363
United States of America

David Marshall
Cell Phone:
Office Phone: (404)592-9980
Email: dmarshall@peteatlanta.com

VINCE TIANO

Vehicle Summary

Unit		Chassis	
Model:	Model 389	Fr Axle Load (lbs):	14600
Type:	Full Truck	Rr Axle Load (lbs):	40000
Description 1:	MODA 389 SLEEPER	G.C.W. (lbs):	54600
Description 2:	58 INCH		
Application		Road Conditions:	
Intended Serv.:	Wrecker	Class A (Highway)	100
Commodity:	Other Commodity	Class B (Hwy/Mtn)	0
		Class C (Off-Hwy)	0
		Class D (Off-Road)	0
Body		Maximum Grade:	6
Type:	Wrecker	Wheelbase (in):	327
Length (ft):	21	Overhang (in):	90
Height (ft):	13.5	Fr Axle to BOC (in):	92.8
Max Laden Weight (lbs):	1000		
Trailer		Cab to Axle (in):	234.2
No. of Trailer Axles:	0	Cab to EOF (in):	324.2
Type:		Overall Comb. Length (in):	448
Length (ft):	0		
Height (ft):	0	Special Req.	
Kingpin Inset (in):	0		
Corner Radius (in):	0		
Restrictions			
Length (ft):	65		
Width (in):	102		
Height (ft):	13.5		

Approved by: _____

Date: _____

Note: All sales are F.O.B. designated plant of manufacture.

Price Level: January 1, 2019
Deal: MODA 389 SLEEPER
Printed On: 4/17/2020 8:20:09 AM

Date: April 17, 2020
Quote Number: QUO-633907-F4K4P4



Sales Code	Std/Opt	Description	\$ List	Weight
Base Model				
0003891	S	Model 389 The Model 389 embodies the Peterbilt heritage and merges it with a proven design to create a legendary classic for vocational applications. The lightweight, all-aluminum cab with lap seam construction, aircraft grade fasteners and bulkhead style doors is legendary for its durability. The pod-mounted headlamps are durable, corrosion-resistant and cost-effective to replace. Peterbilt's all-aluminum cab is not only extremely durable, it's also lightweight to allow for increased payloads to maximize performance and profitability.	186,078	14,915
0091200	O	Other Commodity	0	0
0093110	O	Wrecker Truck with recovery body used for recovering and towing stranded vehicles and equipment.	0	0
0095250	O	Wrecker A truck used to move disabled, improperly parked, impounded, or indisposed motor vehicle.	0	0
0098170	S	United States Registry Canadian Registry Package Requires Air Conditioning Excise Tax Canada, Speedometer to be KPH ipo MPH, Daytime Running Lights and Rubber Battery Pad in Bottom of Battery Box.	0	0
Configuration				
0200700	O	Not Applicable Secondary Manufacturer	0	0
Frame & Equipment				
0514080	O	10-3/4" Steel Rails 403-444" 10.75x3.5x.375 Dimension, 2,136,000 RBM; Yield Strength: 120,000 psi. Section Modulus: 17.8 cubic inches. Weight: 1.74 lbs/inch pair	933	743
0601500	O	Full Steel Inner Liner	1,411	908
0611250	O	Heavy-Duty Iron Front Spring Brackets Forward and Rear	298	35
0620500	O	Frame Components Bolted IPO Huck Fastened	81	0
0633405	O	Additional Frame Drilling	571	0
0644090	O	EOF Square without Crossmember End-of-frame square without crossmember. For use with body builder installed crossmember.	-31	-64
0651090	O	Omit Rear Mudflaps and Hangers	-57	-25
Front Axle & Equipment				
1011970	O	Dana Spicer D1461I 14,600 lb, 3.5 in. Drop Axle features an integrated air disc brake (IADB) knuckle to improve braking and reduce maintenance for IADB applications. The axles are	446	43

Price Level: January 1, 2019

Deal: MODA 389 SLEEPER

Printed On: 4/17/2020 8:20:09 AM

Date: April 17, 2020

Quote Number: QUO-633907-F4K4P4



Sales Code	Std/ Opt	Description	\$ List	Weight
		designed for applications with a gross axle weight rating (GAWR) from 10,000 to 14,600 pounds. IADB feature eliminates separate torque plate and fasteners. One piece forged design includes tie rod arm, torque plate and spindle. The forged knuckle adds reliability for turn angles and the unique design features improved durability and camber alignment.		
1112150	O	Taper Leaf Springs, Shocks 14,600 lb Hendrickson Taper Leaf Springs, shocks 14,6000 lb.	304	57
1233050	O	Power Steering TRW TAS85 TRW TA85 Power Steering for use with 14,600 lb. axle ratings. Glidekote splines on steering shaft extend service life of components.	256	16
1250180	S	Power Steering Reservoir Frame Mounted The power steering reservoir is a steering system that eases drivability by applying hydraulic pressure to the steering gear.	0	0
1354850	O	PHP10 Iron PreSet PLUS Hubs-Air Disc Preset iron hub assemblies are designed for demanding conditions and require less maintenance while still offering dependability and superior performance. Precisely engineered to minimize roller stress under heavy loads and increase bearing life when used in demanding conditions such as wide-based single wheels and misalignment due to spindle wear.	52	42
1354870	O	Severe Service Disc Brake Rotor For refuse applications, providing the braking torque necessary to slow or stop the vehicle.	78	97
1380070	O	Greasable Front Spring Pins	49	0
1380290	S	Bendix Air Disc Front Brakes Bendix air disc front brakes use a floating caliper design to provide foundation braking on all axles and complies with reduced stopping distance regulations.	0	0
1391380	U	10 MM FRONT SPRING SPACER BLOCKS	0	0
Rear Axle & Equipment				
1523310	O	Dana Spicer DSH40 40,000 lb, High Performance 40 Interaxle diff lock air rocker occupies space of one gauge. Laser factory axle alignment to improve handling & reduce tire wear. Magnetic rear axle oil drain plug captures & holds any metal fragments in drive axle lube to extend service life. Parking brakes on all drive axles for optimal performance. Cognis EMGARD® FE 75W-90 synthetic axle lube provides over 1% fuel economy improvement. Reduces wear & extends maintenance intervals, resulting in increased uptime. Provides improved fluid flow to protect components in extreme cold conditions & withstand the stress from high temperatures, extending component life.	694	179
1616300	O	PHP10 Iron PreSet PLUS Hubs	-102	0
1616310	O	Severe Service Disc Brake Rotor Severe Service Disc Brake Rotor for refuse applications.	129	14
1680500	O	SBM Valve Full trucks require a spring brake modulation (SBM) system for emergency braking application. This system requires an SBM valve and a relay valve with spring brakes on the rear axles. The SBM valve	219	0

Price Level: January 1, 2019

Deal: MODA 389 SLEEPER

Printed On: 4/17/2020 8:20:09 AM

Date: April 17, 2020

Quote Number: QUO-633907-F4K4P4



Sales Code	Std/ Opt	Description	\$ List	Weight
		allows the foot valve to operate the rear axle spring brakes if a failure exists in the rear air system.		
1680950	O	Stability System Not Selected Or Not Available	-101	0
1682430	O	Anti-Lock Braking System (ABS) 4S4M ABS-6. Includes air braking system.	-434	-30
1684200	S	Synthetic Axle Lubricant All Axles Peterbilt heavy duty models include Fuel Efficient Cognis EMGARD FE75W-90 which provides customers performance advantages over current synthetic lubricants with reduced gear wear and extended maintenance intervals, resulting in increased uptime. In addition, the lubricant provides improved fluid flow to protect gears in extreme cold conditions and withstand the stress from high temperatures, extending component life.	0	0
1687040	O	Air Disc Rear Brakes, Tandem Drive Axle Includes Automatic Slack Adjusters.	1,557	0
1687090	O	Diff Lock Tandem Axles With Speed Interlock. Automatically Disengages Wheel Diff Lock at Speeds Above 25 mph.	1,974	60
1703900	O	Ratio 3.90 Rear Axle	0	0
1821640	U	Peterbilt Air Trac 46,000 lbs, 54in Axle Spacing	1,799	205
1920385	O	Air Springs, Internal Bumpers Air Trac / Air Leaf suspensions	59	0
1920450	O	Locate Single Leveling Valve Forward Drive Axle of Peterbilt Air Suspension (not avail with Low Air Leaf Susp or Low Low Air Leaf Susp)	46	0
1922260	O	Dash Mtd Dump Switch with Indicator Light Dash mounted dump switch with indicator light for suspension.	46	2

Engine & Equipment

2059987	O	X15 505V 505@1950 GOV@2000 1650@1150	7,016	340
		Performance Series, Vocational Vehicle (2017 Emissions) Includes aluminum flywheel housing. Chevron Delo LE SAE 10W30 engine oil is specially formulated for new low emissions engines. Magnetic engine oil drain plug captures and holds any metal fragments in engine oil to extend service life.		
		N21350 C121 75....Maximum Accelerator Vehicle		
		N21370 C128 75....Maximum Cruise Control Speed		
		N21460 C132 1100..PTO Maximum Engine Speed		
		N21520 C133 5.....Idle Shutdown Timer		
		N21610 C188 40....Idle Shutdown Cold Ambient A		
		N21630 C190 80....Idle Shutdown Hot Ambient Ai		
		N21510 C225 NO....Idle Shutdown with Parking B		
		N21450 C231 NO....Gear Down Protection		
		N21570 C233 YES....Idle Shutdown Manual Overrid		
		N21440 C234 NO....Engine Protection Shutdown		
		N21480 C238 NO....Cruise Control and Engine Br		
		N21470 C239 NO....Cruise Control Auto-Resume		

Price Level: January 1, 2019

Deal: MODA 389 SLEEPER

Printed On: 4/17/2020 8:20:09 AM

Date: April 17, 2020

Quote Number: QUO-633907-F4K4P4



Sales Code	Std/ Opt	Description	\$ List	Weight
		N21590 C382 YES...Idle Shutdown Hot Ambient Au		
		N21530 C396 YES...Idle Shutdown Warning Period		
		N21540 C397 30....Idle Shutdown Warning Period		
		N21320 C399 120...Green House Gas Vehicle Spee		
		N21620 C189 60....Idle Shutdown Intermediate A		
		N21550 C206 0.....Idle Shutdown Percent Engine		
		N21340 C209 120...Maximum Vehicle Speed		
		N21430 C333 0.....Driver Initiated OverrideMax		
		N21410 C334 0.....Driver Initiated Override Ma		
		N21500 C395 0.....Green House Gas Automatic En		
		N21400 C400 474...Driver Initiated Override Re		
		N21420 C401 10....Green House Gas Vehicle Spee		
		N21330 C402 0.....Green House Gas Vehicle Spee		
2091310	O	Engine Idle Shutdown Timer Disabled	0	0
2091315	O	Enable EIST Ambient Temp Overrule	0	0
2091372		Eff EIST NA Expiration Miles	0	0
2091640		Effective VSL Setting NA	0	0
2092013	O	Typical Operating Speed 60 MPH	0	0
2092032	O	Powertrain Optimized for Performance Best analysis for vehicles used in vocational applications or with heavy GCWRs.	0	0
2092039	O	Does not meet Cummins Gearing Recommendations	0	0
2140150	O	Remote PTO and Throttle Provision 12-pin connector on engine harness.	67	0
2140200	S	CARB Engine Idling Compliance PACCAR PX-7, PX-9 and MX, Cummins X15 and ISX diesel engines will include the required factory installed serialized sticker on the drivers door to identify them as meeting the NOx idling standard.	0	0
2140340	O	Remote EOF Throttle Control Plumbed Through Parking Brakes	214	4
2513070	O	200 Amp Alternator, Standard Brush Bosch Long Haul Extreme, standard brush, 170-200 Amps. Dual internal cooling fans, and externally-mounted rectifier and regulator.	161	0
2521090	S	Immersion Type Block Heater 110-120V Standard location for 2.1M and 1.9M models is left-hand under cab, Model 520 is in bumper, and for Model 220 it is at the driver step. Plug includes a weather-proof cover that protects the receptacle. This pre-heater keeps the coolant in the engine block from freezing when the engine is not running.	0	0
2522110	O	PACCAR 12V Starter, N/A PACCAR MX Engines PACCAR 12-volt electrical system. With centralized power distribution incorporating plug-in style relays. Circuit protection for serviceability, 12-volt light system w/circuit protection circuits number & color coded.	322	0

Price Level: January 1, 2019

Deal: MODA 389 SLEEPER

Printed On: 4/17/2020 8:20:09 AM

Date: April 17, 2020

Quote Number: QUO-633907-F4K4P4



Sales Code	Std/ Opt	Description	\$ List	Weight
2538050	O	4 PACCAR Premium 12V Dual Purpose Batt 2920 CCA Threaded stud type terminal. Stranded copper battery cables are double aught (00) or larger to reduce resistance.	229	62
2539410	O	Battery Jumper Terminal Mounted Under Hood LH Frame Rail. Not available with PX-7 engines.	150	4
2539740	O	Kissling Battery Disconnect Switch, 300 amp Mounted on battery box	541	3
2621000	O	2-Speed Fan Clutch For Frequent Start/Stops A 2-speed fan clutch is ideal for vocational applications where the fan clutch engagement time exceeds 10% of the engine run time. When the fan clutch is disengaged, the fan still rotates at 15-25% of the engine RPM. This fan rotation provides crucial airflow to the engine and draws virtually no horsepower.	322	0
2723220	O	Naturally Aspirated 18.7 CFM Air Compressor X15 Only	0	0
2812170	O	Intebrake (Furnished on Engine) Features a dedicated cam lobe design for optimum power and three-stage engine brake operation.	0	0
2921110	S	PACCAR Fuel/Water Separator Standard Service PACCAR Fuel/Water separator standard service intervals. High efficiency media protects critical engine components.	0	0
2921220	O	Fuel Heat for Fuel Filter	54	0
2921320	O	12V Heat for Fuel Filter Fuel filter heaters help ensure a seamless flow of diesel from the tank to the combustion chamber. Eliminating any possibility of moisture freezing within the fuel filter while simultaneously increasing the fuel temperature for atomization within the engine.	66	0
3010400	O	Engine Protection Shutdown Includes oil pressure, oil temperature, coolant temperature, and intake manifold temperature.	6	0
3114270	S	High Efficiency Cooling System Cooling module is a combination of steel and aluminum components, with aluminum connections to maximize performance and cooling capability. Silicone radiator & heater hoses enhance value, durability, & reliability. Constant tension band clamps reduce leaks. ClimaTech extended life coolant extends maintenance intervals which reduces maintenance costs. Anti-freeze effective to -30 degrees F helps protect the engine. Low coolant level sensor warns of low coolant condition to prevent engine damage. Radiator Size by Model: 579/367 FEPTO 1325 sq in, 567/365/367: 1440 sq in, 365 FEPTO: 1184 sq in, 389/367 HH: 1669 sq in, 348: 1000 sq in, 520: 1242 sq in.	0	0
3212010	O	(2) 13" SS Air Cleaners, Cowl Mtd, SS Caps	960	46
3365340	O	Exhaust Dual Side of Cab, LH Side of Cab Stack Aesthetic Only, DPF/SCR right-hand under cab	2,493	110
3381770	O	Curved Tip Standpipe(s)	51	1
3381790	O	Chrome Finish Over Elbows for Dual Exhaust	480	13

Price Level: January 1, 2019

Deal: MODA 389 SLEEPER

Printed On: 4/17/2020 8:20:09 AM

Date: April 17, 2020

Quote Number: QUO-633907-F4K4P4



Sales Code	Std/ Opt	Description	\$ List	Weight
2538050	O	4 PACCAR Premium 12V Dual Purpose Batt 2920 CCA Threaded stud type terminal. Stranded copper battery cables are double aught (00) or larger to reduce resistance.	229	62
2539410	O	Battery Jumper Terminal Mounted Under Hood LH Frame Rail. Not available with PX-7 engines.	150	4
2539740	O	Kissling Battery Disconnect Switch, 300 amp Mounted on battery box	541	3
2621000	O	2-Speed Fan Clutch For Frequent Start/Stops A 2-speed fan clutch is ideal for vocational applications where the fan clutch engagement time exceeds 10% of the engine run time. When the fan clutch is disengaged, the fan still rotates at 15-25% of the engine RPM. This fan rotation provides crucial airflow to the engine and draws virtually no horsepower.	322	0
2723220	O	Naturally Aspirated 18.7 CFM Air Compressor X15 Only	0	0
2812170	O	Intebrake (Furnished on Engine) Features a dedicated cam lobe design for optimum power and three-stage engine brake operation.	0	0
2921110	S	PACCAR Fuel/Water Separator Standard Service PACCAR Fuel/Water separator standard service intervals. High efficiency media protects critical engine components.	0	0
2921220	O	Fuel Heat for Fuel Filter	54	0
2921320	O	12V Heat for Fuel Filter Fuel filter heaters help ensure a seamless flow of diesel from the tank to the combustion chamber. Eliminating any possibility of moisture freezing within the fuel filter while simultaneously increasing the fuel temperature for atomization within the engine.	66	0
3010400	O	Engine Protection Shutdown Includes oil pressure, oil temperature, coolant temperature, and intake manifold temperature.	6	0
3114270	S	High Efficiency Cooling System Cooling module is a combination of steel and aluminum components, with aluminum connections to maximize performance and cooling capability. Silicone radiator & heater hoses enhance value, durability, & reliability. Constant tension band clamps reduce leaks. ClimaTech extended life coolant extends maintenance intervals which reduces maintenance costs. Anti-freeze effective to -30 degrees F helps protect the engine. Low coolant level sensor warns of low coolant condition to prevent engine damage. Radiator Size by Model: 579/367 FEPTO 1325 sq in, 567/365/367: 1440 sq in, 365 FEPTO: 1184 sq in, 389/367 HH: 1669 sq in, 348: 1000 sq in, 520: 1242 sq in.	0	0
3212010	O	(2) 12" SS Air Cleaners, Cowl Mtd, SS Caps	960	46
3365340	O	Exhaust Dual Side of Cab, LH Side of Cab Stack Aesthetic Only, DPF/SCR right-hand under cab	2,493	110
3381770	O	Curved Tip Standpipe(s)	51	1
3381790	O	Chrome Finish Over Elbows for Dual Exhaust	480	13

Price Level: January 1, 2019
Deal: MODA 389 SLEEPER
Printed On: 4/17/2020 8:20:09 AM

Date: April 17, 2020
Quote Number: QUO-633907-F4K4P4



Sales Code	Std/ Opt	Description	\$ List	Weight
		Requires DPF tool box right-hand under cab, and battery box left-hand under cab.		
3387880	O	7" Dia Chrome Plated Steel Standpipe(s) IPO 5"	220	0
3387890	O	36" Ht, 5" Dia Chrome, Clear Coat Standpipe(s)	90	4
Transmission & Equipment				
4040850	O	Eaton RTLO16918B 18-Speed Includes external oil-to-water cooler and internal pump, rear transmission support, direct shift pattern. Synthetic lubricant to reduce friction, improve efficiency, & extend component life. Magnetic transmission oil drain plug captures & holds any metal fragments in transmission oil to extend service life. Torque limiting clutch brake. Forward ratios: LL-14.4, L-12.29, 1st-8.56, 14th-1.00, 15th-0.86, 16th-0.73. Reverse ratios: R1-15.06, R2-12.85, R3-4.03, R4-3.43	2,571	120
4211530	O	SPL250 Lite HT Driveline, 2 Midship Bearings	1,419	240
4216330	O	SPL170 XL Driveline Interaxle Dana Spicer Life Series heavy-duty drive shafts are built for heavy loads over the long haul. For tandem rear axles.	343	5
4250790	O	Aluminum Transmission Bell Housing IPO Iron Eaton transmission 1450 torque and above	83	-52
4250800	U	Manual Shifter, Chrome	123	0
4256250	O	Heavy Duty Input Bearing for PTO Operation For use with Fuller RTLO transmission 1100 through 2250 series. The roller style input shaft bearing has twice the dynamic radial load capability of the ball bearing style and is recommended for transmissions that will be equipped with a transmission mounted 6 or 8 bolt PTO.	39	0
4380220	O	Pre-Damped Clutch Pre-damped feature consists of a set of small springs around the hub, which dampen the engine torsional vibrations at idle speeds before they can reach the transmission and cause gear rattle. Option required on configurations specifying an ISX15 Family 1 engine and a manual transmission with torque ratings of 1650 lb-ft torque or higher.	128	0
4380270	O	Remote Lube Hoses For Clutch Linkage, Release Bearing and cross shafts, mounted to left-hand frame rail	287	6
4380360	O	Upgrade Clutch Torque Capacity Requires 1,550 or greater engine torque.	301	0
Air & Trailer Equipment				
4510320	S	Bendix AD-IS Air Dryer, Heater Bendix Air Treatment Oil Coalescing filter, extended purge. Collects and removes solid, liquid and vapor contaminants before they enter the air brake system.	0	0
4520420	O	Pull Cords All Air Tanks	7	1
4540220	O	Wire Braid Brake Hose, Rear	166	15

Price Level: January 1, 2019
Deal: MODA 389 SLEEPER
Printed On: 4/17/2020 8:20:09 AM

Date: April 17, 2020
Quote Number: QUO-633907-F4K4P4



Sales Code	Std/ Opt	Description	\$ List	Weight
4540260	O	Wrecker AE Connection EOF On Moveable Crossmember Dash mounted air toggle valve plumbed to service brakes, steering column mounted hand valve plumbed to EOF air lines, 7-way socket (occupies the space of one gauge), winch brake switch on dash	485	17
4540420	S	Nylon Chassis Hose	0	0
4543320	S	Steel Painted Air Tanks All air tanks are steel with painted finish except when Code 4543330 Polish Aluminum Air Tanks is also selected (then exposed air tanks outside the frame rails will be polished aluminum). Peterbilt will determine the optimal size and location of required air tanks. Narratives requesting a specific air tank size or location will not be accepted for factory installation. See ECAT to determine number or location of air tanks installed.	0	0
4543330	O	Aluminum Polished Air Tanks Outside Frame Rails Exposed air tanks outside the frame rails will be polished aluminum. Air tanks mounted inside the frame rails or covered by other components will be either painted aluminum (4543340) or painted steel (4543320) air tanks depending on air tank option selected.	348	0
4611930	O	Body Connections 5' BOC Junction box contains light and power circuits for body connections located 5' from back-of-cab	188	6
Tires & Wheels				
5058030	O	FF: MN 16ply 12R22.5 XZE Diameter= 42.6 inches; SLR= 19.8 inches	703	52
5166630	O	RR: BR 16ply 11R24.5 M726ELA Diameter= 44.2 inches; SLR= 20.6 inches	1,840	256
5190008	S	Code-rear Tire Qty 08	0	0
5220520	O	FF: Alcoa 89U637 22.5 X 9.00 Clean Buff Finish Aluminum, Ultra ONE wheels with MagnaForce alloy that saves more than 50 lbs. versus a comparable steel wheel. Built for refuse, logging, mining and other heavy haul applications that demand a tough wheel. Each wheel offers a 10,000 lbs. load rating.	523	-36
5320540	O	RR: Alcoa 98U637 24.5X8.25 Clean Buff Finish Aluminum, Ultra ONE wheels with MagnaForce alloy.	1,724	-120
5390008	S	Code-rear Rim Qty 08	0	0
5407640	O	FF: Polished Wheels, Outer Surface, Sgl/Tdm Steer Polish outer surface of outer wheel. Without chrome wheel nuts.	52	0
5407660	O	RR: Polished Wheels, Outer Surface, Tandem Drive Polish outer surface of outer wheels (4). Without chrome wheel nuts.	209	0
5409680	O	Schrader 1126 Double Seating Extensions Schrader on tire valve extensions provide a seal against contaminants while extending the valve mouth for convenient access. Fits standard .305-32" valve cap threads. Maximum operating pressure, 150 psi.	11	0

Price Level: January 1, 2019

Deal: MODA 389 SLEEPER

Printed On: 4/17/2020 8:20:09 AM

Date: April 17, 2020

Quote Number: QUO-633907-F4K4P4



Sales Code	Std/ Opt	Description	\$ List	Weight
Fuel Tanks				
5552190	O	26" Aluminum 100 Gallon Fuel Tank RH BOC Paddle handle filler cap with threadless filler neck. Top draw fuel plumbing reduces chance of introducing air into the fuel system during low fuel level conditions due to the central placement of fuel pickup tube. Wire braid fuel lines increase durability & reduce potential for leaks.	353	9
5554160	O	26" Aluminum 90 Gallon Fuel Tank LH U/C Includes steps for cab access. Paddle handle filler cap with threadless filler neck. Top draw fuel plumbing reduces chance of introducing air into the fuel system during low fuel level conditions due to the central placement of fuel pickup tube. Wire braid fuel lines increase durability & reduce potential for leaks.	372	20
5602090	O	Location LH U/C 90 Gallon	0	0
5603100	O	Location RH BOC 100 Gallon	0	0
5650310	O	Fuel Tank Fill Center Not available on under cab fuel tanks	0	0
5650540	O	Polish (1) Non-Slip Fuel Tank Step, U/C Tank Only	29	0
5650820	O	Polish (2) Aluminum Fuel Tanks	468	0
5652830	O	Polish All Fuel / Hydraulic Tank Straps Does not apply to rectangular DEF tank straps	83	0
5652890	S	DEF Tank Mounted LH BOC Models 220 and 520 mounted left hand back-of-cab.	0	0
5652990	S	Standard DEF to Fuel Ratio 2:1 Or Greater	0	0
5653000	O	Polished Stainless Steel Cover For DEF Tank	208	0
5655029	O	DEF Tank Medium	84	22
Battery Box & Bumper				
6010670	O	Aluminum Space Saver Battery Box LH BOC Battery access from side	29	-20
6030150	O	Rubber Battery Pad In Bottom of (1) Battery Box Mat in box that holds batteries only	12	4
6030540	O	Polish Battery/Tool Box(s), Aftertreatment Cab Entry complete	334	0
6040550	S	Aftertreatment Aluminum Non-Slip Cab Entry Aftertreatment right-hand under cab step. DPF/SCR for diesel engines, catalyst for natural gas engines. On Models 579 specifying chassis fairings, the box is aerodynamic.	0	0
6121090	S	Steel Bumper Deep Tapered Chromed Two tow points	0	0
6132450	O	Heavy Duty External Tow Eye	777	42

Price Level: January 1, 2019
Deal: MODA 389 SLEEPER
Printed On: 4/17/2020 8:20:09 AM

Date: April 17, 2020
Quote Number: QUO-633907-F4K4P4



Sales Code	Std/Opt	Description	\$ List	Weight
IPO Standard				
Cab & Equipment				
6510140	S	Alum Cab 123in BBC Alum Hood SFFA fenders w/polished crown, spring tilt assist. Proprietary anti-blow-down locking mechanism that keeps hood open during servicing & prevents unintentional closing. Hood latch each side secures hood to cowl. Proprietary all-alum cab is light weight & durable for long service life. One-piece roof reduces potential for leaks. Two-piece windshield for cost effective windshield replacement. Lap seam construction & aircraft fasteners has greater clamp load than rivets. Bulkhead style doors provide virtually water-tight, rattle-free performance. Extruded alum door frames for strength & durability. Full length, heavy-duty piano-type stainless steel door hinges & pins provide durability. View window in RH door for safety. Electric windshield wipers & washers w/intermittent wiper function. Grab handles mtd on cab LH & RH for cab access. Convex mirror over RH door & below each rear view mirror for improved visibility & safety.	0	0
6540660	O	SmartSound Cab Insulation Package Cab acoustic insulation package for day cabs. Includes insulated inside firewall, top side floor damping, absorber treated kick panels, and insulated backwall and roof structure.	375	65
6540740	O	Peterbilt Keyless Entry The Peterbilt key fob functions to lock or unlock the vehicle. With a single click, the drivers door is locked or unlocked and with a double click all doors are locked or unlocked. The third button, depicted by a picture of a lamp, will start the exterior light self-test sequence, helpful when performing the daily pre-trip inspection.	167	2
6701800	O	58" Low Roof Sleeper w/Platinum Interior Includes single LH full-length door, storage tray, door actuated baggage compartment light, rubber floor mats in baggage compartment, sleeper curtain, bunk restraint, wide walk-through opening with upholstered cover, cab/sleeper air suspension, 28.5 in x 78 in premium mattress, 12V DC power outlet, floor carpet, (2) local reading/spot lights, single dome light, fluorescent light, LH/RH full-length closets with overhead storage, closet enclosures, premium bunk trim, cigar lighter and ashtray, digital alarm clock, TV shelf with antenna and wiring, fluorescent light, (1) 12V DC power outlet, heater/air conditioner with air filter and controls in sleeper, cigar lighter and ashtray, digital alarm clock, and (2) two-way vents.	13,482	890
6800360	O	Rubber Fender Lips 2" Wide	116	8
6810730	O	RH Sleeper Baggage Door Includes door-actuated baggage compartment light. Available on 44"/58"/72"/80" sleepers.	223	10
6812590	O	Polished Stainless Steel Sleeper Vents	37	0
6814250	O	Thermal Insulation Pkg 44" & 58" Low Roof Sleeper The thermal insulation package is designed to make the compartment thermally efficient in extreme temperatures. Models 579 and 567	35	4

Price Level: January 1, 2019

Deal: MODA 389 SLEEPER

Printed On: 4/17/2020 8:20:09 AM

Date: April 17, 2020

Quote Number: QUO-633907-F4K4P4



Sales Code	Std/ Opt	Description	\$ List	Weight
		include thick closed-cell foam in the floor carpet and fiber insulation in the walls and roof structure. Models 389, 386, 384, 367 and 365 include thick closed-cell foam in the floor and special mylar-faced foam in the walls and roof structure.		
6911700	S	Peterbilt UltraRide Driver Seat	0	0
6921700	S	Peterbilt UltraRide Passenger Seat	0	0
6930230	O	Seat Skirt - All Eligible Air Seats	35	2
6930580	O	Drivers Armrests - LH & RH	79	4
6930590	O	Passenger Armrest - LH only Required with Evolution LX seats, optional with Evolution ST Seats.	40	2
6939400	S	Air Ride Driver	0	0
6939420	S	High Back Driver	0	0
6939470	S	Vinyl Driver	0	0
6939500	O	Air Ride Passenger Air Ride Passenger is available on all Model 567's.	232	43
6939520	S	High Back Passenger	0	0
6939570	S	Vinyl Passenger	0	0
7001610	O	Leather Steering Wheel	127	0
7039220	O	Platinum Interior - Arctic Gray Platinum Interior - Arctic Gray offers striking charcoal A & B instrument panels and high-gloss burlwood C & D instrument panels, monochromatic color-coordinated dash that is glare-resistant, charcoal soft-touch upper, bright bezel on gauges, high-gloss burlwood insert on contoured doorpads with vinyl inserts, left hand and right hand door mounted map pockets with built-in courtesy lights, power windows & door locks on both doors, adjustable steering column with 18" soft-touch steering wheel, soft-touch steering column cover, floor carpet, padded premium vinyl headliner w/insert, (2) inside sunvisors (integral vanity mirrors), (2) coat hooks, (2) dome/reading lights, footwell lighting, integrated "dead pedal", (5) inside entry grab handles, cupholder & map bin in dash, 12V power outlet dash mounted, and Peterbilt SmartNav System (occupies the space of six gauges). Includes SmartNav Audio System. SmartNav and associated options DO NOT apply to Glider Kits.	3,783	33
7040150	O	Rubber Floor IPO Carpet (Black Only) Rubber Floor Covering in Cab. Standard in Prestige interior, optional in Platinum/Premier interiors.	-42	-6
7210200	O	Fixed Rear Window Back of Sleeper Dark Tint Includes curtains.	164	30

Price Level: January 1, 2019

Deal: MODA 389 SLEEPER

Printed On: 4/17/2020 8:20:09 AM

Date: April 17, 2020

Quote Number: QUO-633907-F4K4P4



Sales Code	Std/ Opt	Description	\$ List	Weight
7230350	O	2-Piece Flat Windshield	12	0
7322010	S	Combo Fresh Air Heater/Air Conditioner With radiator mounted condenser, dedicated side window defrosters, Bi-Level Heater/Defroster Controls, 54,500 BTU/HR, and silicone heater hoses.	0	0
7322130	O	Cup Holder (Floor Mounted) Includes two standard-size drink holders and one extra-large jugholder, coin tray, and clipboard-size storage area.	70	4
7330700	S	Peterbilt Comfort Control - Cab	0	0
7330710	O	Peterbilt Comfort Control - Sleeper	126	2
7410040	O	Outside Sunvisor - Stainless Steel Not available with 2.1M high roof sleeper.	295	4
7561180	O	Aero Mirrors Ea Side Htd & Mtrzd 4-Way Adjustable Bright Finish with Convex	565	4
7610800	O	(4) Round Air Horns Chrome-(2) 30" & (2) 37.5" with polished horn shields.	1,409	33
7725740	O	Midlevel Speaker Package For Cab (4) Speakers	197	6
7725780	O	Midlevel Speaker Package For Sleeper (2) Speakers w/Subwoofer	380	34
7740100	O	Cobra 40 Channel CB Radio w/Integral Speaker Includes illuminated front panel	251	11
7748500	O	CB Antenna Mounting, LH Mirror Available with Rami only on 1.9m, available without Rami on medium duty	20	0
7748510	O	CB Antenna Mounting, RH Mirror Available with Rami only on 1.9m, available without Rami on medium duty	20	0
7748650	O	RAMI Multiband Antenna System - Dual Includes (2) 48 inch antennas.	140	4
7788055	S	SmartLINQ Remote Diagnostics SmartLINQ is Peterbilts proprietary remote diagnostics service which monitors the engine and aftertreatment for diagnostic codes providing real-time code analysis maximizing vehicle uptime and strengthening the fleets partnership with their dealer. SmartLINQ provides fault coverage for over 800 codes, a customizable email notification for 116 codes plus a web portal to manage your entire fleet included at no additional charge. SmartLINQ is compatible with any telematics system and doesnt require a specific fleet management system. For those whose customers utilize PeopleNet, the pre-wire with remote diagnostics will provide a more integrated solution utilizing the existing SmartLINQ modem. For those whose customers utilize other fleet services products, the existing pre-wire option for the other fleet service devices will continue to be available. Standard on Class 8 engines and available on Models 348, 337, 330 and 325 with a PX-9, PX-7 or Cummins Westport natural gas engine.	0	0

Price Level: January 1, 2019

Deal: MODA 389 SLEEPER

Printed On: 4/17/2020 8:20:09 AM

Date: April 17, 2020

Quote Number: QUO-633907-F4K4P4



Sales Code	Std/ Opt	Description	\$ List	Weight
7788058	O	24 Months SmartLINQ Subscription Cummins Engines.	0	0
7850210	O	Plug-In Auto Reset Circuit Breaker in place of fuses in junction box.	109	0
7851040	O	Removable Bugscreen Behind Grille	180	2
7851480	S	Peterbilt Electric Windshield Wipers With Intermittent Feature.	0	0
7900070	O	Fire Extinguisher, Mounted In Sleeper Baggage Compartment, Hazmat approved UL listed/rated ABC	59	8
7900090	O	Triangle Reflector Kit, Ship Loose Florescent triangle emergency road flares are designed to meet and exceed all DOT standards.	18	13
7900950	O	Backup Alarm Wiring To BOC, 5 Ft Additional Wire	49	6
8011100	O	Main Transmission Temperature Gauge 52mm Round, backlit	56	0
8011140	O	Engine Oil Temperature Located in SmartNav display	0	0
8011150	O	Main Transmission Oil Temperature Located in SmartNav display	21	0
8011220	O	Axle Temperature Gauges, Tandem Drive	178	2
8011390	O	Engine Oil Temperature Gauge	47	0
8012240	O	Guard(s) For Rear Axle Heat Gauge	62	2
8021050	O	Air Restriction Pressure Gauge 52mm Round, backlit	188	0
8021380	S	Air Restriction Indicator Mounted on air cleaner, intake piping, or firewall	0	0
8022150	O	Fuel Filter Restriction Gauge	133	0
8032420	O	Buzzer On Air Suspension Dump Valve Requires dash mounted dump valve (1922260)	10	0
8070120	O	Manifold Pressure, Boost Located in SmartNav display	0	0
8070170	O	DPF Status Located in SmartNav display	0	0
8070180	O	Fuel Economy Located in SmartNav display	0	0
8070190	O	Percent Torque Located in SmartNav display	0	0
8071020	O	Manifold Pressure Gauge	42	2
8071280	O	Suspension Pressure Gauge	55	2
8071870	S	Main Instrumentation Panel, Graphics Display	0	0

Price Level: January 1, 2019

Deal: MODA 389 SLEEPER

Printed On: 4/17/2020 8:20:09 AM

Date: April 17, 2020

Quote Number: QUO-633907-F4K4P4



Sales Code	Std/ Opt	Description	\$ List	Weight
		Includes speedometer with trip odometer, tachometer with hourmeter and outside air temperature display, voltmeter, engine oil pressure, engine coolant temperature, fuel level, primary and secondary air pressure gauges. Includes standard warning light package: high water temperature, low oil pressure, and low air pressure warning lights with audible alarms, high beam, turn signal, low fuel, parking brake, and ice warning indicators; seat belt reminder; rocker switches with long-life LED indicators; multi-function turn stalk with flash-to-pass feature (night mode flashes headlights and marker lights; day mode flashes headlights only), intermittent windshield wiper and headlamp beam control. Hydraulic braked trucks do not include air pressure gauges.		
8072560	O	(1) Additional Dash Switch With Wiring (1) additional dash switch with wiring. Spare 1 and 2 share 15 amp fuse, spares 3, 4, and 5 share 15 amp fuse. Availability subject to dash space.	55	0
8111140	S	Headlights Projector Module Pod Integral Turn Signals	0	0
8121170	O	(5) Marker Lights, Bus LED Bullet	188	0
8131560	O	(2) Peterbilt Fog Lights Recessed in bumper	121	6
8132210	O	(1) 6 in Spotlight, Round Halogen LH (1) 6" spotlight, round halogen left hand side.	125	4
8133110	O	Switch & Wiring F/O Auxiliary Light Under cab/sleeper (15 amp max), includes switch on the dash that will power metri-pack sealed connections at the left-hand / right-hand side of cab at base of the firewall. Bundle panel light harness break outs with firewall harness.	48	2
8133120	O	Switch & Wiring F/O Aux Light On Air Cleaners Includes switch on the dash which will power metri-pack sealed connections at the left-hand / right-hand air cleaner outlets	86	2
8133450	O	(2) Brackets F/O Beacon/Strobe, Roof Mounted (2) brackets for furnished by owner beacon / strobe lights roof mounted. Located above each door toward rear, includes switch and wiring.	238	4
8133500	O	Switch On Dash For Light In Sleeper In addition to standard switch	33	2
8133630	O	Gravel Guard Stainless Steel For bumper mounted fog/driving lights	73	0
8140120	O	Incandescent Square Stop/Turn/Tail/Backup Left-hand / right-hand square end of frame or dropped a-brace	30	9
8153100	O	(1) F/O Load Light, Switch, 10' Wire Coil Under / in cab / sleeper baggage compartment	40	2
Paint				
8500710	O	Standard Paint Color Selection	-200	0
8530780	O	(1) Color Axalta Two Stage - Cab/Hood/Sleeper Base Coat/Clear Coat N85020 A - L0006EY WHITE N85500 CAB ROOF L0006EY WHITE	739	0

Price Level: January 1, 2019

Deal: MODA 389 SLEEPER

Printed On: 4/17/2020 8:20:09 AM

Date: April 17, 2020

Quote Number: QUO-633907-F4K4P4